

LEO

XP 550 BSW II

FEATURES

- Diameter of lens: 165 mm
- Lamp Colour Temperature: 6,700K
- Variable CTO: 3,200-6,700K
- Motorized focus
- Linear CMY color mixing
- 1 x color wheel with 14 fixed colors plus open, and rainbow effect
- 1 x static gobo wheel with 16 gobos plus open
- 1 x rotating gobo wheel with 7 gobos plus open, convenient replacement
- Outside diameter: 22.5mm
- Image diameter: 12mm
- 1 x animation wheel with outstanding water and flame effect, the wheel can be replaced.
- 2x prisms: 8-facets prism+6-facets linear prism, rotatable in both directions and overlayable
- Smooth dimming from 0-100%
- Outstanding strobe effect with variable speed
- Independent frost effect
- 2x fixed clamps for 50mm truss



TECHNICAL SPECIFICATIONS

Specifications

- Light Source: Philips MSD Platinum 500L Flex
- Lamp life: 4,000 hours*
- Beam Mode: 2°-7°
- Spot Mode: 5°-32°
- Wash Mode: 8°-70°

Control

- DMX Channel: 18/19/25/26
- Protocols: DMX512, RDM, Art-Net, sACN
- Firmware upgrade via DMX link or USB Disk

Pan/Tilt

- Pan/Tilt movement: 540°/ 260°
- Pan/Tilt Resolution: 16-bit
- Fixation: Tilt lock

Construction


- Display: LCD display
- Battery backup for user setup without power connection
- Data In/Out: 3-pin and 5-pin XLR, RJ45
- Power In/Out: Power Connector in/out
- Protection Rating: IP20

Electrical and Physical

- Input voltage range: 100-240V~ 50/60Hz
- Power Consumption: 765W
- Dimensions: 402x308x725mm (15.8"x12.1"x28.5")
- F/C Dimensions: 870 x 520 x 950 mm (34.3" x 20.5" x 37.4")
- Weight: 30.5kg (67.2lbs)
- 110kg (242.5lbs)(Dual Loader Case)

(*Lamp's working life depends on the cycle ratio of its usage pattern and other environmental factors, such as dust, oil, temperature, humidity, etc.)

PHOTOMETRICS DIAGRAM




FUNCTIONAL EFFECT


CMY+CTO



Color Wheel



Static Gobo Wheel



Rotating Gobo Wheel




Animation Wheel



8-Facet Prism



6-Facet Linear Prism



Frost Filter



DIMENSIONS

