CONCERT / TOURING

SOLAR IMPULSE

XA-1200 BSWF

FEATURES

- · Diameter of lens:187 mm
- · Standard mode Ra>70
- · High CRI mode Ra>90
- · Switch to high CRI mode with high CRI filter
- · Linear CMY color mixing
- · Variable CTO: 2,700K-6,500K
- · 1 x color wheel with 5 colors plus white
- · 1 x rotating gobo wheel with 6 gobos plus open, convenient replacement

Outside diameter: 37.3mm

Image diameter: 25mm

- · 1 x animation wheel with outstanding water and flame effect, the wheel can rotate and be replaced
- \cdot 1 x 4-facet prism rotating in both directions
- \cdot 2 different frost filters to create and improve the wash effect.
- They can be used independently and overlayed.
- · Motorized linear iris
- \cdot 4 x fast and smooth framing shutters, the position and the angel of each shutter blade can be controlled individually; Each shutter blade can block out light completely, the framing module can be rotated at \pm 45 degrees.
- · 2 x fixed clamps for 50mm truss, and 2 x screw holes for removable clamps for 70mm truss



TECHNICAL SPECIFICATIONS

Specifications

- · Light Source: 1000 W LED Engine
- · Color Temperature: 6,500 K
- · Zoom Range: 5°-50°
- \cdot Total lumen output up to 35,000 lm
- · High CRI mode lumen output up to 24,000lm

Control

- · DMX Channel: 29/34
- · Protocols: DMX512, RDM, Art-Net, sACN
- · Firmware Upgrade via DMX link or USB disk

Pan/Tilt

- · Pan/Tilt movement: 540°/ 270°
- · Pan/Tilt Resolution: 16 bit
- · Fixation: Pan/Tilt lock

Construction


· Display: LCD display

- $\cdot \ \mathsf{Battery} \ \mathsf{backup} \ \mathsf{for} \ \mathsf{user} \ \mathsf{setup} \ \mathsf{without} \ \mathsf{power} \ \mathsf{connection}$
- · Data In/Out: 3-pin and 5-pin XLR, RJ45
- · Power In/Out: Power Connector in/out
- · Protection Rating: IP20

Electrical and Physical

- · Input voltage range: 100-240V~ 50/60Hz
- · Power Consumption: 1,370 W
- · Dimensions: 465 x 352 x 836mm(18.3" x 13.8" x 32.9")
- · F/C Dimensions: 715 x 595 x 905mm (28.1" x 23.4" x 35.6")
- · Weight: 44.9 kg (98.9 lbs)
 - 93.8 kg (206.8 lbs)(Single Loader Case)

PHOTOMETRICS DIAGRAM



























FUNCTIONAL EFFECT

CMY+CTO



Color Wheel













Rotating Gobo Wheel





Animation Wheel Framing Module







Linear Iris





4-Facet Prism Frost Filter







DIMENSIONS

